



Bearing Designation Z(RS)/ZZ(2RS)	Dimension(mm)				Mounting dimensions				Weight (Kg)
	d	D	B	rs	min da(min)	da(max)	Da(max)	ra(max)	
SS684	4	9	2.5	0.1	4.8	/	8.2	0.1	0.0006
SS694	4	11	4	0.15	5.2	/	9.8	0.15	0.0017
SS604	4	12	4	0.2	5.6	/	10.4	0.2	0.0023
SS624	4	13	5	0.2	5.6	/	11.4	0.2	0.003
SS634	4	16	5	0.3	6	/	14	0.3	0.0052
SS685	5	11	3	0.15	6.2	/	9.8	0.15	0.0012
SS695	5	13	4	0.2	6.6	/	11.4	0.2	0.0025
SS605	5	14	5	0.2	6.6	/	12.4	0.2	0.0035
SS625	5	16	5	0.3	7	/	14	0.3	0.005
SS635	5	19	6	0.3	7	/	17	0.3	0.0086
SS686	6	13	3.5	0.15	7.2	/	11.8	0.15	0.0019
SS696	6	15	5	0.2	7.6	/	13.4	0.2	0.0039
SS606	6	17	6	0.3	8	/	15	0.3	0.006
SS626	6	19	6	0.3	8	/	17	0.3	0.0082
SS636	6	22	7	0.3	8	/	20	0.3	0.014
SS687	7	14	3.5	0.15	8.2	/	12.8	0.15	0.0022
SS697	7	17	5	0.3	9	/	15	0.3	0.0053
SS607	7	19	6	0.3	9	/	17	0.3	0.0077
SS627	7	22	7	0.3	9	/	20	0.3	0.0127
SS637	7	26	9	0.3	9	/	24	0.3	0.024
SS688	8	16	4	0.2	9.6	/	14.4	0.2	0.0033

SS698	8	19	6	0.3	10	/	17	0.3	0.0072
SS608	8	22	7	0.3	10	/	20	0.3	0.012
SS628	8	24	8	0.3	10	/	22	0.3	0.017
SS638	8	28	9	0.3	10	/	26	0.3	0.028
SS689	9	17	4	0.2	10.6	/	15.4	0.2	0.0035
SS699	9	20	6	0.3	11	/	18	0.3	0.0085
SS609	9	24	7	0.3	11	/	22	0.3	0.015
SS629	9	26	8	0.3	11	/	24	0.3	0.02
SS639	9	30	10	0.6	13	/	26	0.6	0.037