



<b>Resin retainer</b>	
LMB...UU :	LMB6UU
Ball circuit :	4
Weight(Kg) :	14
LMB...UU-AJ :	LMB6UU-AJ
Ball circuit :	4
Weight :	13.5
LMB...UU-OP :	—
Ball circuit :	—
Weight(Kg) :	—
<b>Nominal shaft diameter</b>	
Inch :	3/8
mm :	9.525
<b>dr</b>	
Inch :	0.375
mm :	9.525
Precision(Inch) :	0/- .00025
Precision(μm) :	0/-6
High(Inch) :	0/- .00040
High(μm) :	0/-9
<b>Major dimensions and tolerance</b>	
D(Inch/mm) :	.6250/15.875
D Tolerance(inch) :	0/- .00050
D Tolerance(μm) :	0/-13
L(Inch/mm) :	.8750/22.225
L Tolerance(inch) :	0/- .008
L Tolerance(μm) :	0/-200
B(Inch/mm) :	.6358/16.15
B Tolerance(Inch) :	0/- .008
B Tolerance(μm) :	0/-200
W(Inch/mm) :	.0390/0.992
D1(Inch/mm) :	.5880/14.935
h(Inch/mm) :	.04/1
h1(Inch/mm) :	—
θ :	—
<b>Eccentricity</b>	
Precision :	.0003/8
High :	.0005/12
Radial clearance (Max) :	-.0001/-3
<b>Basic load rating(kN)</b>	
Dynamic :	225
Static :	314