



<b>Resin retainer</b>	
LMB...UU :	LMB24UU
Ball circuit :	6
Weight(Kg) :	670
LMB...UU-AJ :	LMB24UU-AJ
Ball circuit :	6
Weight :	660
LMB...UU-OP :	LMB24UU-OP
Ball circuit :	5
Weight(Kg) :	570
<b>Nominal shaft diameter</b>	
Inch :	1-1/2
mm :	38.1
<b>dr</b>	
Inch :	1.5
mm :	38.1
Precision(Inch) :	0/- .00035
Precision(μm) :	0/- 8
High(Inch) :	0/- .00050
High(μm) :	0/- 12
<b>Major dimensions and tolerance</b>	
D(Inch/mm) :	60.325/2.3750
D Tolerance(inch) :	0/- .00075
D Tolerance(μm) :	0/- 19
L(Inch/mm) :	3.0000/76.200
L Tolerance(inch) :	0/- .012
L Tolerance(μm) :	0/- 300
B(Inch/mm) :	2.4118/61.26
B Tolerance(Inch) :	0/- .012
B Tolerance(μm) :	0/- 300
W(Inch/mm) :	.0859/2.184
D1(Inch/mm) :	2.2389/56.870
h(Inch/mm) :	.12/3
h1(Inch/mm) :	.75/19.05
θ :	50°
<b>Eccentricity</b>	
Precision :	.0005/12
High :	.0008/20
Radial clearance (Max) :	-.0003-8
<b>Basic load rating(kN)</b>	
Dynamic :	2180
Static :	4020